

USB DAC 仕様

XDA-20



Weight:6.5 KG

Size:W380 x H65 x D260 m

<Digital 入力>

Coaxial, BNC, Optical, AES/EBU

PCM:16-24bit /44.1,48,88.2,96,176.4,192 kHz

DOP:DOP64

I2S

PCM:16-32bit /44.1,48,88.2,96,176.4,192,352.8,384kHz

DSD:DSD64,DSD128,DSD256,DSD512

DOP:DOP64,DOP128 DOP256,DOP512

USB (Windows, Mac, Linux)

16-32bit

44.1,48,88.2,96,176.4,192,352.8,384 kHz

DSD64,DSD128

VIA Network Audiophile Adapter

16-32bit / 44.1,48,88.2,96,176.4,192,352.8,384 kHz

DSD64,DSD128,DSD256

* DSD256 HQPlayer Only

<Analog 出力>

RCA output level: 2.3 Vrms @0dBFS

XLR Output Level: 4.6 Vrms @0dBFS (XLR: 1 Ground, 2 Hot, 3 Cold)

Frequency response: 20-20K Hz +/-0.15dB

Overall Power Consumption:<50W

Channel crosstalk:-138dB @ 1kHz

Frequency Response:20Hz-20kHz +/-0.15dB

S/N:>128dB

THD+N:<0.0005%

1 MD:<0.0005%

Power:AC 100V 50/60Hz

XDA-12



Weight: 4KG

Size:W190 x H70 x D313 mm

<Digital 入力>

DA-X20 に準ずる、ただし I2S 入力: DSD128 まで、BNC 入力なし

<Analog 出力>

RCA output level: 2.5 Vrms @0dBFS

XLR Output Level: 5.0 Vrms @0dBFS (XLR : 1 Ground, 2 Hot, 3 Cold)

Frequency response: 20-20K Hz +/-0.15dB

Overall Power Consumption:<25W

Channel crosstalk:-138dB @ 1kHz

S/N:>128dB

THD+N:<0.0005%

1 MD:<0.0005%

Power:AC 115V 50/60Hz